

# CERTIFICATE OF COMPLIANCE

Certificate Number 20170725-E493156  
Report Reference E493156-20170724  
Issue Date 2017-JULY-25

Issued to: LEDSON Sp.zoo Sp.K  
ul. Przemysłowa 3  
05-082 Blizne Laszczynskiego POLAND

This is to certify that  
representative samples of LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS,  
LUMINAIRES AND FITTINGS  
See Addendum Page


Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 2108, Low Voltage Lighting Systems.  
UL 1598 and CSA C22.2 No.250.0-08, Luminaires.  
UL 8750, Light Emitting Diode (LED) Equipment for Use in  
Lighting Products.  
CSA C22.2 No. 250.13, Light Emitting Diode (LED)  
Equipment for Use in Lighting Products.

Additional Information: See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at <http://www.ul.com/aboutul/locations>




# CERTIFICATE OF COMPLIANCE

Certificate Number 20170725-E493156  
Report Reference E493156-20170724  
Issue Date 2017-JULY-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Ground-mounted recessed Class 2.  
SERIES "DRIVEWAY-XX-YYYYY-Z-W-LL

Where -XX can be G0, G35 or RAL and indicates the profile color; YYYYY can be 824SP, 827SP, 830SP, 840SP or 850SP and indicates the type and color temperature of LED stripe; Z can be O or T and indicates the type of Diffuser; W can be any number between 0.3 and 5 and indicates the profile length in meter; LL can be 0.3m, 0.3mf, 0.5, 1, 1.5 0.5 or 2 and indicates the length and type of supply connection cable.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations>

