

MAXIMUM TEMPERATURE OF THE PROFILE [°C]

AMBIENT TEMPERATURE- 25°C,

PROFILE	6-DURIS	10-5060	12-3528	17-DURIS	30-DURIS	36-DURIS	78-DURIS
	1 m- 9,9 W 860 lm	1 m- 20,1 W 1550 lm	1 m- 7,6 W 700 lm	1 m- 34,7 W 3060 lm	1 m- 34,7 W 3240 lm	1 m- 52,3 W 4890 lm	
	1 LED- 0,08 W 6,8 lm	1 LED- 0,22 W 17,2 lm	1 LED- 0,08 W 7,3 lm	1 LED- 0,48 W 42,4 lm	1 LED - 0,48 W 45,3 lm		1 LED- 0,48 W 45,3 lm
RSL15			35,49				
RSL7			37,17				
SL15			36,45				
SL7			38,57				
ALU-45			36,27				
ALU-CORNER			36				
PL35					50,84		
PLW80						44,42	
RPL35					47,3		
ALU-ROUND		45,77	34,08				
ALU-FLAT		44,49	32,98				
ALU-STAIR		39,23	31,11				
ALU-WALL		39,84	31,1				
ALU-WALL US	32,99	40,4					
SLW8			36,03				
RSLW8			35,59				
SLW15		49,03	34,62				
ALU-CEILING		41,31	31,62				
PLS30				43,47			
RPLS30				44,64			
ALU-SWISS	42,89						
SLW20		44,3					
RSLW20		42,42					
SLW20B		42,56					
PL35S			29,93		41,15		
PL35D			33,83 (2x 12-3528)		46,66 (17-DURIS+ 12-3528)		
ALU-SQUARE			38,2				
SLW10			48,27 (3x 12-3528)				
WALL LED LAMP		44,43 (2x 10-5060)	33,18 (2x 12-3528)	44,93 (17-DURIS+ 12-3528)			
RPLW80						42,26	
ALU-GLASS		36,06	29,53				
ALU-STAIR 2	36,68 (2x 6-DURIS)		35,05 (12-3528+ 6-DURIS)				
ALU-STAIR 2 CARPET	37,02 (2x 6-DURIS)		35,96 (12-3528+ 6-DURIS)				
ALU-TRIANGLE				49,03 (2x 17-DURIS)		36,88	
PLW116						48,6 (2x 36-DURIS)	43,72
ALU-ASYMMETRIC		45,7					
ALU-EPOXY		46,06	33,88	56,64			
RPLW116		41,74 (2x 10-5060)		45,65 (2x 17-DURIS)			
PL55					42,1		

- recommended, - optional

MAXIMUM TEMPERATURE OF THE PROFILE [°C]

AMBIENT TEMPERATURE- 25°C,

PROFILE	6-DURIS	10-5060	12-3528	17-DURIS	30-DURIS	36-DURIS	78-DURIS
	1 m- 9,9 W 860 lm	1 m- 20,1 W 1550 lm	1 m- 7,6 W 700 lm	1 m- 34,7 W 3060 lm	1m- 1 LED -	34,7 W 3240 lm	1 m- 52,3 W 4890 lm
	1 LED- 0,08 W 6,8 lm	1 LED- 0,22 W 17,2 lm	1 LED- 0,08 W 7,3 lm	1 LED- 0,48 W 42,4 lm		0,48 W 45,3 lm	1 LED- 0,48 W 45,3 lm
DPLS		42,74 (10-5060+ 12-3528)	50,04 (17-DURIS+ 12-3528)				
SPL35		38,96		46,29			
ALU-BASEBOARD	34,72						
SPLW116							47,85
ALU- SWISS 20		46,57					
ALU- CEILING WASHER				53,08 (17-DURIS+ 6-DURIS)			
ALU- STAIR NANO	42,9 (2x 6-DURIS)						
DPL55		46,49 (10-5060+ 30-DURIS)	41,8 (12-3528+ 30-DURIS)		41,72 (30-DURIS)		
NANO LINE	44,65						
ALU-ROUND 38				49,15			
ALU-ROUND 52				44,50			
RPL55 FL					43,20		
SPL35 FL				48,25			
RPLW80 FL						41,30	
DPL55 FL					37,89 (30-DURIS+ 17-DURIS)		
PL55 FL					41,70		
PLS33 FL				41,38			
ALU45 WIDE	41,00 (2x 6-DURIS)						
RPL35 FL				47,03			
DPL35 FL				47,20 (17-DURIS+ 2x 6-DURIS)			
SLW20 FL		42,65					
RSLW20 FL		39,60					
DPL70 FL				57,24 (3x 17-DURIS)			
ALU-360	57,81 (6x 3-DURIS)						
RPL35 US				42,94			
RPL55 US					40,15		
RPL70 US						38,75	
PLW70 FL						42,22	
SL15 FL	36,59						

 - recommended,  - optional